



LYNGSOE PHOENIX™ SELF-CHECK KIOSK

SMART RFID SELF-CHECK KIOSK FOR LIBRARIES

SLEEK DESIGN

The Phoenix self-check unit has a high-end design, utilizing high-quality finishes. With its slim, light, spacious and attractive design, the Lyngsoe Phoenix™ self-check kiosk is specifically designed to meet the needs of today's libraries. A glass table is used to create a sense of lightness and to make the device discreet in the library space, while still being a fully functional tabletop for patrons to use for their materials. The design fits all library materials will be placed correctly in the opening with market-leading regrade.

SELF-CHECK WITH NO TOUCHES

As an optional software feature, the patron is able to borrow books with the smartphone and thereby avoiding any touches.

EMPHASIS ON USABILITY AND ERGONOMICS

All hardware – computers, RFID readers, receipt printer – is integrated into the furniture. Fully integrated printer, which is accessible from the front allowing back-to-back placements. The design emphasizes usability and ergonomics for patrons.

BENEFITS

- Super sleek design
- Small footprint
- Optional side table left or right
- Payment devices options
- Large 19" touch screen
- ADA and DDA compliant
- Hook for handbags



SPECIFICATIONS

LYNGSOE PHOENIX™ SELF-CHECK KIOSK

GENERAL

Functions	Check out, Check in, Account info, Renew, Holds, Offline
Item identification	RFID, Barcode or both
Security	RFID (AFI/EAS)
RFID standards	ISO15693 SLIX 18000-3-1
RFID data models	ISO28560, DDM, KATVE, TechLogic, TV2, 3M, TRC, ITG, ITG2
Patron card types	Barcode, RFID, Mifare, Smartphone, QR code
Pin code	Touch screen or separate PIN-pad
Options	Payment devices, optional side table left or right

COMPATIBILITY AND PROGRAMS

Operating system	Windows 10
Software	LibRid3
Connectivity	Protocol TCP/IP, LMS: SIP 1 SIP 2
Manual sorting options	
Reporting and statistics management	
Remote management	
Centralized management system	

TECHNICAL INFORMATION

Touch screen	19"
Printer	80 mm Thermal printer
Input voltage	100-240 V
Power usage	250 W
Dimensions	550 x 500 x 1500 mm / 21" x 21" x 59" (L x W x H)
Unit weight	74 kg / 163 lbs
Color	White
Certificates	CE

